

Type G/GT GRP Encapsulated Hygiene Fire Door

Architectural Specification

Client: Generic (UK/EU)

Brand: Polydoor[®]

Manufacturer: Speedflex UK Ltd

Location: South Wales, UK

Tel: 0800 2888861 **Fax:** 0800 0191799

Email: sales@speedflex.net

Standard Specifications

(December 2012 >)

Door Model:	Type G/GT GRP Encapsulated Hygiene Fire Door
Door Type:	Single Action GRP Door
Waterproof:	Yes
Food Safe:	Yes
Door Colour:	White (Standard)
Optional Colours:	Red, Green, Blue, Yellow & Optional RAL Colours (Subject to Min Qty)
Blade Material:	40mm GRP Gel Coat Finish with Vermiculite Fire Rated Core
Impact Bumpers:	5mm Grey Rubber Lower Sheet Optional 6mm Black Embossed Heat Formed Polypropylene Spring Bumpers 300mm(h) x Custom Width – Spring R=60mm (Approx)
Bumper Colour:	Grey RAL7045 (Smooth)
Optional Colours:	Black (Smooth)
Door Thickness:	40mm
Max Dimensions:	Max 2400mm(w) x 2800mm(h)
Hinges:	4 x Stainless Steel Lift-Off Hinges
Upper Glazing:	Triple Glazed Fire Rated Units 200mm(w) x 800mm(h) - (Other Sizes Available)
Lower DDA Glazing:	Yes Included 200(w) x 300(h) - (Other Sizes Available)
Internal Fixings:	Stainless Steel 304
Availability:	Standard colours 5-6 weeks Please enquire for non-standard colours and alternative specifications

E&OE