

Type H Pallet Truck Loading Door (Double)

Architectural Specification

Client: Generic (UK/EU)

Brand: Polydoor[®]

Manufacturer: Speedflex UK Ltd

Location: South Wales, UK

Tel: 0800 2888861 Fax: 0800 0191799

Email: sales@speedflex.net

Standard Specifications

(December 2012 >)

Door Model:	Polydoor[®] Type H Pallet Truck Loading Door
Door Type:	Dual Action Impact Traffic Door
Waterproof:	Yes
Food Safe:	Yes
Door Colour:	White (Standard)
Optional Colours:	Grey, Red, Green, Blue, Yellow & Custom RAL Colours (All subject to MOQ)
Blade Material:	Solid 15mm HMW500-PE Food Safe Pressed/Planned Polyethylene
Impact Bumpers:	6mm Black Embossed Heat Drape Formed Polypropylene Spring Bumpers 300mm(h) x Custom Width – Spring R=60mm (Approx)
Bumper Quantity:	12no.
Bumper Colour:	Black (Embossed)
Optional Colours:	Black (Smooth)
Safety:	Clear Overlap PVC Central Anti-Finger Trap Protection (Black Optional) Stainless Steel A2 Screw Carrier - (Optional Stainless Steel Dowel System)
Door Thickness:	15mm core / 45mm at hinge location
Blade Support:	Anodised Aluminium Spine / Stainless Steel (Optional)
Max Dimensions:	Double Doors: Max S/O 2500mm(w) x 3000mm(h)
Hinges:	90 Degree Stainless Steel Dual Action Auto-Close - (Hold Open Optional)
Upper Glazing:	15mm Seamless TC Clear Acrylic 400mm(w) x 600mm(h) - (Other Sizes Available)
Lower DDA Glazing:	No
Internal Fixings:	Stainless Steel 304
Mounting Plates:	Aluminium Spine (Mill Finish Full Height) – Pre Drilled (Optional Stainless Steel Spine Available)
Availability:	Standard colours 3-4 weeks Please enquire for non-standard colours and alternative specifications

E&OE